

## Water soluble paper

Purge gas dam with low air permeability for all pipe diameters

It is made from sodium carboxymethyl cellulose and wood fibres and dissolves immediately and completely in water and most liquids. It is 100% biodegradable and leaves no residue in the pipe.

- Forms an excellent insulation for noble gases
- Cost savings due to lower gas consumption, as the paper is placed in close proximity to the welding zone, which means that less shielding gas is required to replace the oxygen from the purge chamber.
- Can be easily attached to the inner wall of the pipe with the water soluble Aquasol adhesive tape, thus forming an airtight barrier

| Part No. | Description         | Unit              | Size           |
|----------|---------------------|-------------------|----------------|
| RG350204 | Water soluble paper | Roll              | 230 mm x 50 m  |
| RG350205 | Water soluble paper | Roll              | 390 mm x 50 m  |
| RG350206 | Water soluble paper | Roll              | 520 mm x 50 m  |
| RG350202 | Water soluble paper | Pack (500 sheets) | 430 x 560 mm   |
| RG350203 | Water soluble paper | Pack (250 sheets) | 390 x 560 mm   |
| RG350209 | Water soluble tape  | Roll              | 25,4 mm x 91 m |


## EZ Zone tape

Clean welding without impurities

EZ Zone Tape is a purge gas masking tape that seals the weld gap between pipes, minimising gas loss during the purge process.

Due to the adhesive-free middle area, welding without contamination is possible.

- Halogen and fluorocarbon free
- Heat resistant
- Reduces pipe cleaning time and the amount of gas used
- Improves safety at your workplace
- Heat resistance up to 260 °C
- Minimum temperature application: -12.5 °C



| Part No. | Size          | Glue free range |
|----------|---------------|-----------------|
| RG350211 | 63 mm x 22 m  | 2.5" x 75'      |
| RG350212 | 101 mm x 22 m | 4.0" x 75'      |



## EZ Tape aluminum tape

Heat-resistant aluminium adhesive tape

EZ Tape is a traditional aluminium tape used for sealing c- measures during purging, as well as for sealing pipe ends for transport. It is coated with a heat resistant acrylic adhesive system against high shear forces.

The tape can be used in many other traditional applications, such as sealing pipes for heating or air conditioning systems. It is also an excellent vapour barrier.

- Halogen-free and fully coated with acrylic adhesive
- Soft film adapts well to irregular surfaces
- Suitable e.g. as a vapour barrier for sealing pipes

| Part No. | Description           | Size         |
|----------|-----------------------|--------------|
| RG350213 | EZ Tape aluminum tape | 50 mm x 20 m |

